



- Current Rating: 1A AC/DC
- Voltage Rating: 100V AC/DC
- Insulation Resistance: 100MΩ Min
- Withstanding Voltage: 300VAC(1Min)
- Contact resistance: 20mΩ(Max).
- Operation Temperature: -40℃ to +105℃

- Insulator (Housing): PA9T (UL94V-0)
- PIN:Phosphor Bronze Tin-Plated
- Welding lug Brass Tin -plated
- Color: Begie

Ordering Information

SCT1012WVS - xx E 1 BE 182

No.of Pins	Insulation	Package	Color
See Table	E=PA9T	1=Tape&Reel	BE=Beige

Poles	Dimensions(mm)		
	A	B	C
2	1.00	4.10	3.30
3	2.00	5.10	4.30
4	3.00	6.10	5.30
5	4.00	7.10	6.30

					OPERATION		DRAW	Yao	2021.07.02	SCALE	—	 SCONДАР ELECTRONIC LIMITED	
		SCONДАР ELECTRONIC, LTD ENGINEER XJ2503			X.X	±0.35	DESIGN	Xiong	2021.07.02	UNIT	mm		
			X.XX	±0.25	CHECK	Lisa		2021.07.02	SIZE	A4			
AO	2021.07.02		NEW	—		—	X.XXX	±0.15	APPROVE				
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle	± 3'	APPROVE			PROJ.		TITLE:	MX501331 1.00mm PA9T V0 xxPin Beige SMT WV Socket tape and reel package MPQ=1500Pcs/Reel
					DIM	TOL							