

RoHS

Specification:

- Current Rating: 3A AC/DC
- Voitage Rating: 250V AC/DC
- Insulation Resistance: 1000MΩ Min
- Withstanding Voltage: 1000VAC(1Min)
- Contact resistance: 20mΩ(Max).
- Operation Temperature: -25℃ to +85℃

Material:

- Insulator (Housing): PBT (UL94V-2)
- Color: Black

Ordering Information

SCT2543HNL - 2xx D BK 116

No.of Pins
See Table

Insulation
D=PBT

Color
BK=Black

东莞市晟凯达电子科技有限公司
工程专用章

受控

2*40	99.06	101.60
2*39	96.52	99.06
2*38	93.98	96.52
⋈	⋈	⋈
2*4	7.62	10.16
2*3	5.08	7.62
2*2	2.54	5.08
Poles	A	B
	Dimensions	

					OPERATION	DRAW	Peng	2021.07.07	SCALE	—	 SCONDAR ELECTRONIC LIMITED	
					X.X ±0.35	DESIGN			UNIT	mm		
					X.XX ±0.25				SIZE	A4		
					X.XXX ±0.15		Lisa	2021.07.07	SHEET	1/1	PART NO.	SCT2543HNL-2xxDBK116
AO	2019.10.15	NEW			Angle ± 3'	APPROVE	Allen	2021.07.07	PROJ.	⌀	TITLE:	Dupont 2.54mm Pitch Housing Connector
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM TOL							