

RoHS

受控

Specification:

- Current Rating: 3A AC/DC
- Voltage Rating: 250V AC/DC
- Insulation Resistance: 1000MΩ Min
- Withstanding Voltage: 1000VAC(1Min)
- Contact resistance: 20mΩ(Max).
- Operation Temperature: -25℃ to +85℃

Material:

- Insulator (Housing): PA66 (UL94V-0)
- PIN Brass/Tin-Plated
- Color: Beige

Ordering Information

SCT2523WV - 2xx B 0 BE 169

No.of Pins
See Table

Insulation
B=PA66 V0

0=PE Bag

Color
BE=Beige

Poles	Dimensions		Poles	Dimensions	
	A	B		A	B
2x02	2.50	7.50	2x12	27.50	32.50
2x03	5.00	10.00	2x13	30.00	35.00
2x04	7.50	12.50	2x14	32.50	37.50
2x05	10.00	15.00	2x15	35.00	40.00
2x06	12.50	17.50	2x16	37.50	42.50
2x07	15.00	20.00	2x17	40.00	45.00
2x08	17.50	22.50	2x18	42.50	47.50
2x09	20.00	25.00	2x19	45.00	50.00
2x10	22.50	27.50	2x20	47.50	52.50
2x11	25.00	30.00			

PCB Layout

SCONDAR ELECTRONIC,LTD
ENGINEER 2505

SCONDAR

SCONDAR ELECTRONIC LIMITED

SCT2523WV-2xxB0BE169

XHD2.50mm PA66 V0 Beige 2xxPin Brass Tin-plated
DIP WV Sokcet Bag