



SPECIFICATIONS

Current Rating: 0.5A AC,DC
 Voltage Rating: 30V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 200V AC/minute
 Pin Material: Phosphor Bronze/Tin orGold-plated
 Solder Tabs: Phosphor Bronze/Tin orGold-plated
 Material: Nylon or LCP ,UL94V-0
 Color: Natural(Beige)

PART NO.	Dimensions		
	A	B	C
SCT0800WR-S-02P	0.80	3.80	1.82
SCT0800WR-S-03P	1.60	4.60	2.62
SCT0800WR-S-04P	2.40	5.40	3.42
SCT0800WR-S-05P	3.20	6.20	4.22
SCT0800WR-S-06P	4.00	7.00	5.02
SCT0800WR-S-07P	4.80	7.80	5.82
SCT0800WR-S-08P	5.60	8.60	6.62
SCT0800WR-S-09P	6.40	9.40	7.42
SCT0800WR-S-10P	7.20	10.20	8.22
SCT0800WR-S-11P	8.00	11.00	9.02
SCT0800WR-S-12P	8.80	11.80	9.82
SCT0800WR-S-13P	9.60	12.60	10.62
SCT0800WR-S-14P	10.40	13.40	11.42
SCT0800WR-S-15P	11.20	14.20	12.22
SCT0800WR-S-18P	13.60	16.60	14.62
SCT0800WR-S-20P	15.20	18.20	16.22
SCT0800WR-S-24P	18.40	21.40	19.42

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	YANG	2016.01.25	SCALE	UNIT	mm	PART NO.	SCT0800WR-S-XXP
1	16/01/25	底部增加两个扣点	YANG	MICKY	~ 10 ±0.15	DESIGN			SIZE	A4		TITLE:	0.8 IDC 90C SMT WF
0	05/12/27	NEW			20 ~ 30 ±0.30	CHECK	MICKY	2016.01.25	SHEET	1/1		DRAWING NO.	SCT0800
					30 ~ ±0.50	APPROVE	ALLEN	2016.01.25	PROJ.				
					Angle ± 2'								
					DIM TOL								

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED