



SPECIFICATIONS
 Current Rating: 0.5A AC,DC
 Voltage Rating: 30V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 200V AC/minute
 Pin Material: Phosphor Bronze/Tin-plated
 Solder Tabs: Phosphor Bronze/Tin-plated
 Material: Nylon 6T,UL94V-0
 Cap: Nylon 6T,UL94V-0,Natural(Beige)
 Color: Natural(Beige)

PART NO.	Dimensions	
	A	B
SCT0800WV-S-02P	0.80	3.80
SCT0800WV-S-04P	2.40	5.40
SCT0800WV-S-08P	5.60	8.60
SCT0800WV-S-10P	7.20	10.20
SCT0800WV-S-12P	8.80	11.80
SCT0800WV-S-14P	10.40	13.40
SCT0800WV-S-15P	11.20	14.20
SCT0800WV-S-16P	12.00	15.00
SCT0800WV-S-17P	12.80	15.80
SCT0800WV-S-20P	15.20	18.20

					OPERATION	DRAW	Micky.Liu	2006/05/02	SCALE		森康达电子有限公司 S'CONDAR ELECTRONIC LIMITED		
					~ 10 ±0.15	DESIGN			UNIT	mm			
					20 ~ 30 ±0.30		CHECK	Judy.Huang	2006/05/02	SIZE		A4	PART NO.
0	05/12/27	NEW			30 ~ ±0.50	APPROVE	Hellen.Li	2006/05/02	SHEET	1/1		TITLE:	0.8 IDC 180C SMT WF
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle ± 2'	APPROVE			PROJ.		DRAWING NO.	SCT0800	