

SPECIFICATIONS


Voltage rating: 200V AC, DC
 Current rating: 0.5A, AC, DC (AWG#30)
 Withstanding Voltage: 500V AC/minute
 Insulation resistance: 100MΩ min
 Temperature range: -40°C - +80°C
 Contact resistance: 20mΩ

HOUSING

Part No: SCT1004H-30
 Poles: 30
 Material: Nylon 46, UL94V-0

TERMINAL

Lock: Stainless steel
 Reinforce slice: Stainless steel

						OPERATION	DRAW	Judy.Huang	2006/05/02	SCALE		 森康达电子有限公司 S'CONDAR ELECTRONIC LIMITED		
						~ 10 ±0.15	DESIGN			UNIT	mm			
						20 ~ 30 ±0.30	CHECK	Micky.Liu	2006/05/02	SIZE	A4		PART NO.	SCT1004H-30P
						30 ~ ±0.50	APPROVE	Hellen.Li	2006/05/02	SHEET	1/1		TITLE:	FI-E 1.0mm
0	05/12/27		NEW			Angle ± 2'	APPROVE			PROJ.	◆	DRAWING NO.	SCT1004	
REV	DATE		MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM TOL								