



SPECIFICATIONS
 Current Rating: 1A AC,DC
 Voltage Rating: 150V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Brass/Tin-plated
 Solder Tabs: Phosphor Bronze/Tin-plated
 Cap: Nylon 6T,UL94V-0,Natural(Beige)
 Water: Nylon 6T,UL94V-0
 Color: Natural(Beige)

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
SCT1252WV-SF-02PB	1.25	4.15	6.25
SCT1252WV-SF-03PB	2.50	5.40	7.50
SCT1252WV-SF-04PB	3.75	6.65	8.75
SCT1252WV-SF-05PB	5.00	7.90	10.00
SCT1252WV-SF-06PB	6.25	9.15	11.25
SCT1252WV-SF-07PB	7.50	10.40	12.50
SCT1252WV-SF-08PB	8.75	11.65	13.75
SCT1252WV-SF-09PB	10.00	12.90	15.00
SCT1252WV-SF-10PB	11.25	14.15	16.25
SCT1252WV-SF-11PB	12.50	15.40	17.50
SCT1252WV-SF-12PB	13.75	16.65	18.75
SCT1252WV-SF-13PB	15.00	17.90	20.00
SCT1252WV-SF-14PB	16.25	19.15	21.25
SCT1252WV-SF-15PB	17.50	20.40	22.50

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SCALE	PART NO.	TITLE:	DRAWING NO.
0	05/12/27	NEW			~ 10 ∠ ± 2'	DESIGN	mm	SCT1252WV-SF-XXPB	DF13 1.25 SMT 180C 1*NP WF	SCT1252WV-SF
1					20 ~ 30 ∠ ± 2'	CHECK	A4			
					30 ~	APPROVE	1/1			
					Angle	Simon				
					∠ ± 2'	Micky.Liu				
					± 2'	Hellen.Li				
					± 2'	2014.12.25				
					± 2'	2014.12.25				

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED