



■ SPECIFICATIONS

- Voltage rating: 100V AC, DC
- Current rating: 1A, AC, DC (AWG28)
- Withstanding voltage: 500V AC/minute
- Insulation resistance: 500MΩ min
- Temperature range: -25°C - +85°C
- Contact resistance: 20mΩ max

■ HOUSING

- Part No. :SCT1253H-XX
- Poles:2-30
- Material:Nylon 66+15% Glass Fibre, UL94V-0
- Q' TY: 1,000 pcs/reel

NO	PART NO	DIMENSION(mm)	
		A	B
1	SCT1253H-02	1.25	4.45
2	SCT1253H-03	2.50	5.70
3	SCT1253H-04	3.75	6.95
4	SCT1253H-05	5.00	8.20
5	SCT1253H-06	6.25	9.45
6	SCT1253H-07	7.50	10.70
7	SCT1253H-08	8.75	11.95
8	SCT1253H-09	10.00	13.20
9	SCT1253H-10	11.25	14.45
10	SCT1253H-11	12.50	15.70
11	SCT1253H-12	13.75	16.95
12	SCT1253H-13	15.00	18.20
13	SCT1253H-14	16.25	19.45
14	SCT1253H-15	17.50	20.70
15	SCT1253H-16	18.75	21.95

NO	PART NO	DIMENSION(mm)	
		A	B
16	SCT1253H-17	20.00	23.20
17	SCT1253H-18	21.25	24.45
18	SCT1253H-19	22.50	25.70
19	SCT1253H-20	23.75	26.95
20	SCT1253H-21	25.00	28.20
21	SCT1253H-22	26.25	29.45
22	SCT1253H-23	27.50	30.70
23	SCT1253H-24	28.75	31.95
24	SCT1253H-25	30.00	33.20
25	SCT1253H-26	31.25	34.45
26	SCT1253H-27	32.50	35.70
27	SCT1253H-28	33.75	36.95
28	SCT1253H-29	35.00	28.20
29	SCT1253H-30	36.25	39.45

					OPERATION	DRAW			SCALE		森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
					~ 10 ±0.15	DESIGN			UNIT	mm		
					20 ~ 30 ±0.30	CHECK			SIZE	A4	PART NO.	SCT1253H-XX
0	05/12/27				30 ~ ±0.50	APPROVE			SHEET	1/1	TITLE:	HRS DF14 1.25 HOUSING
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle ± 2'				PROJ.	⌀	DRAWING NO.	SCT1253
					DIM TOL							