


Recommended P.C.B Layout(Top Side)
(Tolerance=±0.05)



SPECIFICATIONS

Voltage Rating:100V AC/DC

Current Rating:1A AC/DC

Withstanding Voltage:800V AC/minute

Insulation Resistance:1,000MΩ min.

Temperature Range:-25° C - +85° C

Contact Resistance:20mΩ max

HOUSING

Part No: SCT2005WV-XXP

Poles:2-16

Material:PA 66, UL94V-0

PART NO	DIMENSION	
	A	B
SCT2005WR-02	2.00	6.00
SCT2005WR-03	4.00	8.00
SCT2005WR-04	6.00	10.00
SCT2005WR-05	8.00	12.00
SCT2005WR-06	10.00	14.00
SCT2005WR-07	12.00	16.00
SCT2005WR-08	14.00	18.00
SCT2005WR-09	16.00	20.00
SCT2005WR-10	18.00	22.00
SCT2005WR-11	20.00	24.00
SCT2005WR-12	22.00	26.00
SCT2005WR-13	24.00	28.00
SCT2005WR-14	26.00	30.00
SCT2005WR-15	28.00	32.00
SCT2005WR-16	30.00	34.00

OPERATION	DRAW	YANG	2015.12.08	SCALE		SCONDAR 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
~ 10 ±0.15	DESIGN			UNIT	mm		
20 ~ 30 ±0.30		CHECK	Micky.Liu	2015.12.08	SIZE	A4	PART NO.
30 ~ ±0.50	APPROVE	Allen	2015.12.08	SHEET	1/1	TITLE:	JAE2.0 90C WAFER
Angle ± 2° DIM TOL	APPROVE			PROJ.	◆	DRAWING NO.	SCT2005WR