


SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 500MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

TERMINAL

Part No: SCT2507MT
 Wire Range: AWG#22-#28 (OD1.8mm)
 Material: Brass
 Finish: Tin Plated
 Thickness: 0.25mm
 Q`TY: 10,000PCS/Reel

						OPERATION	DRAW	CHENA	2010.12.03	SCALE		 森康达电子有限公司 S'CONDAR ELECTRONIC LIMITED	
						~ 10 ±0.15	DESIGN			UNIT	mm		
						20 ~ 30 ±0.30	CHECK	MICKY	2010.12.03	SIZE	A4	PART NO.	SCT2507MT
						30 ~ ±0.50	APPROVE	HELLEN	2010.12.03	SHEET	1/1	TITLE:	JST2.5 MALE TERMINAL
0	05/12/27		NEW			Angle ± 2'				PROJ.	↯	DRAWING NO.	SCT2507
REV	DATE		MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM TOL							