



SPECIFICATIONS

Voltage Rating:250V AC/DC
 Current Rating:2A AC/DC
 Withstanding Voltage:500V AC/minute
 Insulation Resistance:800MΩ min.
 Temperature Range:-25°C – +85°C
 Contact Resistance:20mΩ max

HOUSING

Part No: SCT2508MH-XXP
 Poles:2-4
 Material:Nylon 66,UL94V-2

PART NO	DIMENSION			
	A	B	C	D
SCT2508MH-02	2.50	5.90	7.40	2.90
SCT2508MH-03	5.00	8.40	10.00	5.40
SCT2508MH-04	7.50	10.90	12.50	7.90

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	Judy.Huang	2006/05/02	SCALE
0	05/12/27	NEW			~ 10 ±0.15	DESIGN			UNIT mm
					20 ~ 30 ±0.30	CHECK	Micky.Liu	2006/05/02	SIZE A4
					30 ~ ±0.50	APPROVE	Hellen.Li	2006/05/02	SHEET 1/1
					Angle ± 2'				TITLE: Molex 5102 HOUSING
					DIM TOL				DRAWING NO. SCT2508



PART NO.	SCT2508MH-XXP
TITLE:	Molex 5102 HOUSING
DRAWING NO.	SCT2508