


SPECIFICATIONS


Voltage Rating:250V AC/DC  
 Current Rating:2A AC/DC  
 Withstanding Voltage:500V AC/minute  
 Insulation Resistance:800MΩ min.  
 Temperature Range:-25°C - +85°C  
 Contact Resistance:20mΩ max

TERMINAL


Part No:SCT2508MT  
 Wire Range:AWG#22-#28(OD1.80mm)  
 Material:Brass  
 Finish:Tin Plated  
 Thickness:0.2mm  
 Q'TY:10,000PCS/Reel



B-B



A-A

						OPERATION	DRAW	Judy.Huang	2006/05/02	SCALE		 <b>森康达电子有限公司</b> SCONDAR ELECTRONIC LIMITED	
						~ 10 ±0.15	DESIGN			UNIT	mm		
						20 ~ 30 ±0.30	CHECK	Micky.Liu	2006/05/02	SIZE	A4	PART NO.	SCT2508MT
0	05/12/27		NEW			30 ~ ±0.50	APPROVE	Hellen.Li	2006/05/02	SHEET	1/1	TITLE:	Molex 5240 TERMINAL
REV	DATE		MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle DIM ± 2' TOL				PROJ.	◆	DRAWING NO.	SCT2508