



Section A-A

Section B-B

SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 4A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

TERMINAL

Part No: SCT2541MT
 Wire Range: AWG#22-#28 (OD1.55mm)
 Material: Brass
 Finish: Tin Plated
 Q'TY: 10,000PCS/Reel

| | | | | | | | | | | | | | |
|-----|------|--------------------------|--|--------|---------|---------------|---------|-------|------------|-------|-----|---|-----------------|
| | | | | | | OPERATION | DRAW | YANG | 2016.03.21 | SCALE | | 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED | |
| | | | | | | ~ 10 ±0.15 | DESIGN | | | UNIT | mm | | |
| | | | | | | 20 ~ 30 ±0.30 | CHECK | MICKY | 2016.03.21 | SIZE | A4 | PART NO. | SCT2541MT |
| | | | | | | 30 ~ ±0.50 | APPROVE | ALLEN | 2016.03.21 | SHEET | 1/1 | TITLE: | MX2.54 TERMINAL |
| REV | DATE | MODIFICATION DESCRIPTION | | CHANGE | APPROVE | Angle DIM | | | | PROJ. | | DRAWING NO. | SCT2541MT |