



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING

Part No: SCT2544HB-XXPB
 Poles: 2-20
 Material: PA66, UL94V-2

PART NO.	Dimensions		PART NO.	Dimensions	
	A	B		A	B
SCT2544HB-02PB	2.54	5.08	SCT2544HB-13PB	30.48	33.02
SCT2544HB-03PB	5.08	7.62	SCT2544HB-14PB	33.02	35.56
SCT2544HB-04PB	7.62	10.16	SCT2544HB-15PB	35.56	38.10
SCT2544HB-05PB	10.16	12.70	SCT2544HB-16PB	38.10	40.64
SCT2544HB-06PB	12.70	15.24	SCT2544HB-17PB	40.64	43.18
SCT2544HB-07PB	15.24	17.78	SCT2544HB-18PB	43.18	45.72
SCT2544HB-08PB	17.78	20.32	SCT2544HB-19PB	45.72	48.26
SCT2544HB-09PB	20.32	22.86	SCT2544HB-20PB	48.26	50.80
SCT2544HB-10PB	22.86	25.40			
SCT2544HB-11PB	25.40	27.94			
SCT2544HB-12PB	27.94	30.48			

					OPERATION	DRAW	CHENA	2010.02.11	SCALE		森康达电子有限公司 SCONDAR ELECTRONIC LIMITED		
					~ 10 ±0.15	DESIGN			UNIT	mm			
					20 ~ 30 ±0.30	CHECK	MICKY	2010.02.11	SIZE	A4		PART NO.	SCT2544HB-XPB
0	05/12/27				30 ~ ±0.50	APPROVE	HELLEN	2010.02.11	SHEET	1/1		TITLE:	MX2.54 CD-ROM HOUSING
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle ± 2° DIM TOL	APPROVE	HELLEN	2010.02.11	PROJ.	◆	DRAWING NO.	SCT2544HA	