



**SPECIFICATIONS**  
Voltage Rating: 250V AC/DC  
Current Rating: 3A AC/DC  
Withstanding Voltage: 1500V AC/minute  
Insulation Resistance: 1000MΩ min.  
Temperature Range: -25° C - +85° C  
Contact Resistance: 20mΩ max

**WAFER**  
Part No: SCT2544WV-XXPC  
Poles: 2-12  
Material: PBT+GF15%  
Pin: Brass/Gold plated

PART NO.	Dimensions	
	A	B
SCT2544WV-02PC	2.54	7.62
SCT2544WV-03PC	5.08	10.16
SCT2544WV-04PC	7.62	12.70
SCT2544WV-05PC	10.16	15.24
SCT2544WV-06PC	12.70	17.78
SCT2544WV-07PC	15.24	20.32
SCT2544WV-08PC	17.78	22.86
SCT2544WV-09PC	20.32	25.40
SCT2544WV-10PC	22.86	27.94
SCT2544WV-11PC	25.40	30.48
SCT2544WV-12PC	27.94	33.02

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	YANG	2016.05.11	SCALE	UNIT	mm	PART NO.	SCT2544WV-XXPC
0	05/12/27	NEW			~ 10 ±0.15	DESIGN			SIZE	A4		TITLE:	MX2.54 CD-ROM 180C WAFER
					20 ~ 30 ±0.30	CHECK	MICKY	2016.05.11	SHEET	1/1		DRAWING NO.	SCT2544
					30 ~ ±0.50	APPROVE	ALLEN	2016.05.11	PROJ.				
					Angle ± 2'								
					DIM TOL								

