



DIM D
2.50mm
2.90mm

SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

Part No: SCT25441WVA-2xXXP
 Poles: 2x3-20
 Material: PBT 94V-0
 Pin Material: Brass/Gold-flash or Tin-plated

PART NO.	Dimensions		
	A	B	C
SCT2544WVA-2x03P	5.08	10.12	8.12
SCT2544WVA-2x04P	7.62	12.66	13.20
SCT2544WVA-2x05P	10.16	15.20	15.74
SCT2544WVA-2x06P	12.70	17.74	18.28
	---	---	---
SCT2544WVA-2x19P	45.72	50.76	48.76
SCT2544WVA-2x20P	48.26	53.30	51.30

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SCALE	UNIT	SIZE	SHEET	TITLE	DRAWING NO.
0	05/12/27	NEW			~ 10 ±0.15	Judy.Huang	2006/05/02	mm	A4	1/1	SCT2544WVA-2xXXP	SCT2544WVA-2xXXP
					20 ~ 30 ±0.30						MOLEX2.54 WAFER	
					30 ~ ±0.50	Micky.Liu	2006/05/02					
					Angle ± 2'	Hellen.Li	2006/05/02					
					DIM TOL							

