



SPECIFICATIONS

- Poles:3P
- Voltage rating:250V AC/DC
- Current rating:2.5A, AC/DC
- Withstand voltage:1000V AC/minute
- Temperature range:-25° C+95° C
- Insulation resistance:1000M Ω min

- Part No.:SCT2546MH-03P
- Material:NYLON66 UL94V0
- Q' ty:1000pcs./bag

| | | | | | | | | | | | | | |
|-----|----------|--|--------------------------|--------|---------|---------------|---------|--|--|-------|---|--|--------------------------|
| | | | | | | OPERATION | DRAW | | | SCALE | |  森康达电子有限公司 SCONDAR ELECTRONIC LIMITED | |
| | | | | | | ~ 10 ±0.15 | DESIGN | | | UNIT | mm | | |
| | | | | | | 20 ~ 30 ±0.30 | CHECK | | | SIZE | A4 | PART NO. | SCT2546H5-3P |
| 0 | 05/12/27 | | NEW | | | 30 ~ ±0.50 | APPROVE | | | SHEET | 1/1 | TITLE: | Dupont2.54 3P H5 Housing |
| REV | DATE | | MODIFICATION DESCRIPTION | CHANGE | APPROVE | Angle ± 2' | | | | PROJ. |  | DRAWING NO. | SCT2546 |
| | | | | | | DIM TOL | | | | | | | |