



Ordering Information & Specifications

PART NO.	Wire Range	Insulation O.D.	Material	Finish
SCT3001FTPC	AWG#20-#24	1.85mm(max)	Phosphor Bronze	Tin-plated
SCT3001FTHG	AWG#20-#24	1.85mm(max)	Phosphor Bronze	Gold-flash
SCT3001FTHG G1	AWG#20-#24	1.85mm(max)	Phosphor Bronze	Gold-plated 15u"
SCT3001FTHG G2	AWG#20-#24	1.85mm(max)	Phosphor Bronze	Gold-plated 30u"

Note:E-Stamping before Tin-plated or Gold-plated

OPERATION	DRAW	Judy.Huang	2006/05/02	SCALE
~ 10 ±0.15	DESIGN			UNIT mm
20 ~ 30 ±0.30	CHECK	Micky.Liu	2006/05/02	SIZE A4
30 ~ ±0.50	APPROVE	Hellen.Li	2006/05/02	SHEET 1/1
Angle ± 2'	APPROVE			PROJ.
DIM TOL				

SCONDAR 森康达电子有限公司
SCONDAR ELECTRONIC LIMITED

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	PART NO.	TITLE:	DRAWING NO.
0	05/12/27	NEW			SCT3001FTPC	MX3.0 FEMALE TERMINAL	SCT3001