



SPECIFICATIONS

Voltage Rating: 250V AC/DC

Current Rating: 7A AC/DC

Withstanding Voltage: 1500V AC/minute

Insulation Resistance: 1000MΩ min.

Temperature Range: -25° C - +85° C

Contact Resistance: 20mΩ max

TERMINAL

Part No: SCT3960T

Wire Range: AWG#18-#24 (OD2.8mm max)

Material: **Brass**

Finish: Tin Plated

Thickness: 0.25mm

Q'TY: 5,000PCS/Reel

						OPERATION	DRAW	CHENA	2005.03.13	SCALE		森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
						~ 10 ±0.15	DESIGN			UNIT	mm		
						20 ~ 30 ±0.30	CHECK	MICKY	2005.03.13	SIZE	A4	PART NO.	SCT3960T
0	05/12/27		NEW			30 ~ ±0.50	APPROVE	HELLEN	2005.03.13	SHEET	1/1	TITLE:	MOLEX3.96 TERMINAL
REV	DATE		MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle DIM	APPROVE	HELLEN	2005.03.13	PROJ.		DRAWING NO.	SCT3960