



The height of the combined

NOTES:
 Insulator Material: PBT, UL 94V-0
 Contact Plating: Gold flash over nickel
 Contact Material: Brass or Phosphor bronze
 Current Rating : 1A AC,DC
 Voltage Rating:250V AC,DC
 Contact Resistance: 20MΩ Max.
 Dielectric Withstanding: AC 500V
 Insulator Resistance: 1000MΩ Min.
 Operating Temp.: -40°C~+105°C

PART NO	Dim. A	Dim. B
IDC200NH1260-3-6P	11.2	4.0
IDC200NH1260-3-8P	13.2	6.0
IDC200NH1260-3-10P	15.2	8.0
IDC200NH1260-3-12P	17.2	10.0
IDC200NH1260-3-14P	19.2	12.0
IDC200NH1260-3-16P	21.2	14.0
IDC200NH1260-3-18P	23.2	16.0
IDC200NH1260-3-20P	25.2	18.0
IDC200NH1260-3-22P	27.2	20.0
IDC200NH1260-3-24P	29.2	22.0
IDC200NH1260-3-26P	31.2	24.0
IDC200NH1260-3-28P	33.2	26.0
IDC200NH1260-3-30P	35.2	28.0
IDC200NH1260-3-34P	39.2	32.0
IDC200NH1260-3-36P	41.2	34.0
IDC200NH1260-3-40P	45.2	38.0
IDC200NH1260-3-44P	49.2	42.0
IDC200NH1260-3-50P	55.2	48.0
IDC200NH1260-3-60P	65.2	58.0

					OPERATION	DRAW	SIMON	2014.12.26	SCALE		森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
					~ 10 ±0.15	DESIGN			UNIT	mm		
					20 ~ 30 ±0.30		CHECK	VICKY	2014.12.26	SIZE		A4
0		NEW			30 ~ ±0.50	APPROVE	ALLEN	2014.12.26	SHEET	1/1		PART NO.
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle DIM	± 2' TOL			PROJ.		TITLE:	2.00 IDC Three-piece
											DRAWING NO.	IDC200NH1260-3-2xXXP