RoHS

NOTE 1:
UL Standard
1. Rated voltage/Rated current:300V/10A
2. Withstanding Voltage:AC1600V/Min
3. Wire range:26～14AWG
IEC Standard
1. Rated voltage/Rated current: 280V/18A
2. Wire range : 0.5～2.5mm^2
NOTE 2:
1. Pitch: 5.00mm
2. Operating temperature: -40℃～+105℃
3. Stripping length: 7～8mm
4. RoHS Compliance
5. Rated torque:4.43[Lb. in]

Ordering Information

SCT126V - 5.00-03 B 4 650

- Series NO.
- No.of Pins See Table
- Material B=PA66 V0
- COLOUR
  1. Gray 2. Blue
  3. Black 4. Green
  5. Orange 6. Red
  7. Yellow 8. White

ITEM	NAME OF PART	MATERIAL	NOTES
4	(Cage) 方盒	Copper alloy 铜合金	(Ni plated)镀镍
3	(Contact)触点	Copper alloy 铜合金	(Sn plated)镀锡
2	(Screw) 螺丝 M3	Steel 钢	(Ni plated)镀镍
1	(Housing) 塑件	PA66	UL94V-0

P距方向公差 (mm Pitch range in mm			其他尺寸公差 mm Nominal dimension range in mm					— ⌒ ▱	∠
≤6	6～10	10～24	≤30	30～60	60～100	100～150	>150	0.1/10	±1°
±0.15	±0.20	±0.30	±0.20	±0.30	±0.50	±0.70	±1.00		

DRAW	Zhong	2020.08.02	SCALE	—	SCONDAR ELECTRONIC LIMITED
DESIGN			UNIT	mm	
CHECK	Lisa	2020.08.02	SIZE	A4	
APPROVE	Allen	2020.08.02	SHEET	1/1	PART NO. SCT126V-5.00-03B4650
			PROJ.		TITLE: /