

RoHS

NOTE 1:

UL Standard

1. Rated voltage/Rated current: 300V/20A

2. Withstanding Voltage: AC1600V/Min

3. Wire range: 26~12AWG

IEC Standard

1. Rated voltage/Rated current: 250V/20A

2. Wire range : 2.5mm²

NOTE 2:

1. Pitch: 5.08mm

2. Operating temperature: -40°C~+105°C

3. Stripping length: 7~8mm

4. RoHS Compliance

5. Rated torque: 4.43[Lb. in]

Ordering Information


SCT129V - 5.08-02 B 4 650

Series NO.

No. of Pins
See Table

Material
B=PA66 V0

COLOUR
1. Gray 2. Blue
3. Black 4. Green

4	(Cage) 方盒	Copper alloy 铜合金	(Ni plated) 镀镍	P 垂直公差 (mm) Pitch range in mm								其他尺寸公差 mm Nominal dimension range in mm				DRAW	Zhong	2020.08.02	SCALE	-	 SCONDAR ELECTRONIC LIMITED
3	(Contact) 触点	Copper alloy 铜合金	(Sn plated) 镀锡	≤6	6 ~ 10	10 ~ 24	≤30	30 ~ 60	60 ~ 100	100 ~ 150	> 150	0.1/10	DESIGN			UNIT	mm				
2	(Screw) 螺丝 M3	Steel 钢	(Ni plated) 镀镍	≤6	6 ~ 10	10 ~ 24	≤30	30 ~ 60	60 ~ 100	100 ~ 150	> 150	0.1/10	CHECK	Lisa	2020.08.02	SIZE	A4				
1	(Housing) 塑件	PA66	UL94V-0	±0.15	±0.20	±0.30	±0.20	±0.30	±0.50	±0.70	±1.00	±1'	APPROVE	Allen	2020.08.02	SHEET	1/1	PART NO.	SCT129V-5.08-02B4650		
TEM	NAMF OF PART	MATFRIAL	NOTFS													PROJ.	⌀	TITLE:			