


RoHS

NOTE 1:
 UL Standard
 1. Rated voltage/Rated current: 300V/2A
 2. Withstanding Voltage: AC1600V/Min
 3. Wire range: 30~12AWG
 IEC Standard
 1. Rated voltage/Rated current: 250V/2A
 2. Wire range : 0.2~0.5mm²
 NOTE 2:
 1. Pitch: 2.50mm
 2. Operating temperature: -40℃~+105℃
 3. Stripping length: 8.5~9.5mm
 4. RoHS Compliance

Ordering Information

SCT250A - 2.50 XX B 1 650
 Series NO. No. of Pins See Table Material B=PA66 V0 COLOUR
 1. Gray 2. Blue
 3. Black 4. Green

4	(Cage) 方盒	Copper alloy 铜合金	(Ni plated) 镀镍	距方向公差 mm			其他尺寸公差 mm							DRAW	Zhong	2020.08.02	SCALE	-	 SCONDAR SCONDAR ELECTRONIC LIMITED	
3	(Contact) 触点	Copper alloy 铜合金	(Sn plated) 镀锡	Pitch range in mm			Nominal dimension range in mm							DESIGN			UNIT	mm		
2		Steel 钢	(Ni plated) 镀镍	≤6	6 ~ 10	10 ~ 24	≤30	30 ~ 60	60 ~ 100	100 ~ 150	> 150	0.1/10		CHECK	Lisa	2020.08.02	SIZE	A4		
1	(Housing) 塑件	PA66	UL94V-0	≤6	6 ~ 10	10 ~ 24	±0.20	±0.30	±0.50	±0.70	±1.00	±1'		APPROVE	Allen	2020.08.02	SHEET	1/1		PART NO.
TEM	NAMF OF PART	MATFRIAL	NOTFS	±0.15	±0.20	±0.30	±0.20	±0.30	±0.50	±0.70	±1.00	±1'		PROJ.			PROJ.	⊕	TITLE:	/