

RoHS



NOTE 1:

UL Standard

1. Rated voltage/Rated current:300V/8A

2. Withstanding Voltage:AC1600V/Min

3. Wire range:22~16AWG

IEC Standard

1. Rated voltage/Rated current: 320V/10A

2. Wire range : 0.2~1.5mm²

NOTE 2:

1. Pitch: 3.50mm

2. Operating temperature: -40℃~+105℃

3. Stripping length: 8.5~9.5mm

4. RoHS Compliance

Ordering Information


SCT250A - 3.50 XX B 1 650

Series NO.

No.of Pins
See Table

Material
B=PA66 V0

COLOUR
1. Gray 2. Blue
3. Black 4. Green

4	(Cage) 方盒	Copper alloy 铜合金	(Ni plated) 镀镍	距方向公差 mm			其他尺寸公差 mm					DRAW	Zhong	2020.08.02	SCALE	-	 SCONDAR ELECTRONIC LIMITED		
3	(Contact) 触点	Copper alloy 铜合金	(Sn plated) 镀锡	Pitch range in mm			Nominal dimension range in mm					DESIGN			UNIT	mm			
2		Steel 钢	(Ni plated) 镀镍	≤6	6 ~ 10	10 ~ 24	≤30	30 ~ 60	60 ~ 100	100 ~ 150	> 150	0.1/10	CHECK	Lisa	2020.08.02	SIZE		A4	
1	(Housing) 塑件	PA66	UL94V-0	≤6	6 ~ 10	10 ~ 24	±0.20	±0.30	±0.50	±0.70	±1.00	±1'	APPROVE	Allen	2020.08.02	SHEET		1/1	PART NO.
TEM	NAMF OF PART	MATFRIAL	NOTFS	±0.15	±0.20	±0.30	±0.20	±0.30	±0.50	±0.70	±1.00	±1'	PROJ.	☯	TITLE:				