

RoHS

NOTE 1:

UL Standard

1. Rated voltage/Rated current:300V/15A

2. Withstanding Voltage:AC1600V/Min

3. Wire range:28~12AWG

IEC Standard

1. Rated voltage/Rated current: 320V/20A

2. Wire range : 0.5~2.5mm<sup>2</sup>

NOTE 2:

1. Pitch: 5.08mm

2. Operating temperature: -40°C~+105°C

3. Stripping length: 7~8mm

4. RoHS Compliance

5. Rated torque:4.43[Lb. in]

**Ordering Information**

SCT2EDGKM - 5.08-XX B 4 650

Series NO.


No.of Pins  
See Table

Material  
B=PA66 V0

COLOUR  
1. Gray 2. Blue 3. Black

Dimension

II

4	(Cage) 方盒	Copper alloy 铜合金	(Ni plated) 镀镍	P 垂直公差 (mm) Pitch range in mm		其他尺寸公差 mm Nominal dimension range in mm								DRAW	Zhong	2020.08.02	SCALE	-	 SCONDAR ELECTRONIC LIMITED
3	(Contact) 触点	Copper alloy 铜合金	(Sn plated) 镀锡	≤6	6~10	10~24	≤30	30~60	60~100	100~150	>150	0.1/10	DESIGN			UNIT	mm		
2	(Screw) 螺丝 M3	Steel 钢	(Ni plated) 镀镍										CHECK	Lisa	2020.08.02	SIZE	A4		
1	(Housing) 塑件	PA66	UL94V-0										APPROVE	Allen	2020.08.02	SHEET	1/1	PART NO.	
TEM	NAMF OF PART	MATFRIAL	NOTFS	±0.15	±0.20	±0.30	±0.20	±0.30	±0.50	±0.70	±1.00	±1'	PROJ.			TITLE:			