


RoHS

NOTE 1:
 UL Standard
 1. Rated voltage/Rated current:300V/15A
 2. Withstanding Voltage:AC1600V/Min
 3. Wire range:28~12AWG
 IEC Standard
 1. Rated voltage/Rated current: 320V/20A
 2. Wire range : 0.5~2.5mm²
 NOTE 2:
 1. Pitch: 6.35mm
 2. Operating temperature: -40℃~+105℃
 3. Stripping length: 7~8mm
 4. RoHS Compliance
 5. Rated torque:4.43[Lb. in]

Ordering Information

SCT635 - 6.35-02 B 4 650

Series NO. No.of Pins See Table Material B=PA66 V0 COLOUR
 1. Gray 2. Blue
 3. Black 4. Green
 5. Orange 6. Red
 7. Yellow 8. White

4	(Cage) 方盒	Copper alloy 铜合金	(Ni plated) 镀镍	P 距方向公差 (mm) Pitch range in mm		其他尺寸公差 mm Nominal dimension range in mm							DRAW	Zhong	2020.08.02	SCALE	-	 SCONDAR SCONDAR ELECTRONIC LIMITED	
3	(Contact) 触点	Copper alloy 铜合金	(Sn plated) 镀锡	≤6	6 ~ 10	10 ~ 24	≤30	30 ~ 60	60 ~ 100	100 ~ 150	> 150	0.1/10	DESIGN			UNIT	mm		
2	(Screw) 螺丝 M3	Steel 钢	(Ni plated) 镀镍										CHECK	Lisa	2020.08.02	SIZE	A4		
1	(Housing) 塑件	PA66	UL94V-0										APPROVE	Allen	2020.08.02	SHEET	1/1		PART NO.
TEM	NAMF OF PART	MATFRIAL	NOTFS	±0.15	±0.20	±0.30	±0.20	±0.30	±0.50	±0.70	±1.00	±1'	PROJ.			PROJ.	⌀	TITLE:	/