

RoHS

- NOTE 1:
 UL Standard
 1. Rated voltage/Rated current: 300V/30A
 2. Withstanding Voltage: AC3500V/Min
 3. Wire range: 26~10AWG
 IEC Standard
 1. Rated voltage/Rated current: 750V/26A
 2. Wire range : 1.5~4.0mm²
- NOTE 2:
 1. Pitch: 9.50mm
 2. Operating temperature: -40℃~+105℃
 3. Stripping length: 8~9mm
 4. RoHS Compliance
 5. Rated torque: 4.43 [Lb. in]

Ordering Information

SCT950 - 9.50-03 B 4 650

Series NO. No. of Pins See Table Material B=PA66 V0 COLOUR
 1. Gray 2. Blue
 3. Black 4. Green
 5. Orange 6. Red
 7. Yellow 8. White

ITEM	NAMF OF PART	MATFRIAL	NOTFS	P距方向公差 (mm) Pitch range in mm			其他尺寸公差 mm Nominal dimension range in mm					公差	形状	DRAW	Zhong	2020.08.02	SCALE	-	UNIT	mm	SHEET	1/1	PART NO.	SCT950-9.50-03B4650	
				≤6	6~10	10~24	≤30	30~60	60~100	100~150	>150														0.1/10
4	(Cage) 方盒	Copper alloy 铜合金	(Ni plated) 镀镍																						
3	(Contact) 触点	Copper alloy 铜合金	(Sn plated) 镀锡																						
2	(Screw) 螺丝 M3	Steel 钢	(Ni plated) 镀镍																						
1	(Housing) 塑件	PA66	UL94V-0																						
TEM	NAMF OF PART	MATFRIAL	NOTFS	±0.15	±0.20	±0.30	±0.20	±0.30	±0.50	±0.70	±1.00	±1'													

