

A

B

C

D

E

F


G

H

Weight: g/pcs

RoHS Compliant

受控



Technical requirements:
 -100% testing of the product.
 -Compliant with ROHS requirements.
 -Tensile Strength Standard Compliant with UL486A

PIN ASSIGNMENT

P1	Color	P2
1	Red	Tin
2	Black	Tin

NO	PART NO	DESCRIPTION	PCS	1	
NO	PART NO	DESCRIPTION	UNIT	Q'TY	REMARK
4	SCT4500FHA-02CBK109	SM2.50mm PA66 V2 Black 02Pin No Wing Female housing	PCS	1	
3	SCT4500MTSAPS169	EL4.5mm Phosphor Bronze Tin Plated Ultra High foot Male Terminal 18-22AWG	PCS	2	
2	NOUL16TSBKR205	NO-UL 16AWG(252/0.08TS),OD:3.0mm Silicone Wire 200°C 600V,Color:Black	MM	105	
1	NOUL16TSRDSR205	NO-UL 16AWG(252/0.08TS),OD:3.0mm Silicone Wire 200°C 600V,Color:Red	MM	105	

SCONDAR

SCONDAR ELECTRONIC LIMITED

TOLERANCES: $\pm 0.3\text{mm}$ UNIT: mm PAGE/ 1 of 1

Rev A

REV	DESCRIPTION	DATE	ECN NO.	DATE	2026.01.05	SCT P/N	D0010
A	INITIAL RELEASE	2026.01.05		DRAWN BY	Yao	CUSTOMER P/N	
				CHECKED BY	Xiong	CUSTOMER	Drone Wire Harness
				APPROVED BY	Lisa	TITLE: Drone wiring harness/model aircraft battery electrical adjustment connection wire/EL4.50mm 2P Female Housing L=100mm (Can Be Customized)	

SCONDAR ELECTRONIC LTD
ENGINEER

A B C D E F G H