

A

B

C

D

E


F

G



H

Weight: g/pcs

RoHS Compliant



P1



P2

Technical requirements:

- No defects such as short circuit, open circuit, misalignment, etc.
- Compliant with ROHS/RACEH requirements

PIN ASSIGNMENT		
P1	Color	P2
1	Black	Tin
2	Black	Tin
3	Black	Tin
4	Black	Tin
5	Black	Tin

3	HTB-ID200	Heat Shrink Tube Ø:2.0mm Color:Black L:10mm	PCS	5	
2	SCTM12F7M-05AF	M12F Male 05Pin Fixed Socket	PCS	1	
1	JL100724TSBK	UL1007 24AWG(11/0.16TS) OD:1.4mm, PVC Wire Color:Black(Colors Can Be Customized) L= (Can Be Customized)	PCS	5	
NO	PART NO	DESCRIPTION	UNIT	Q'TY	REMARK

REVISIONS

DATE

2024.12.15

SCONDAR ELECTRONIC LIMITED

TOLERANCES: ± 0.3mm

UNIT: mm PAGE/
1 of 1

Rev

A

REV	DESCRIPTION	DATE	ECN NO.
A	INITIAL RELEASE	2024.12.15	

DRAWN BY

Xiong

CUSTOMER P/N

CHECKED BY

Lisa

CUSTOMER

Waterproof Wire Harness

APPROVED BY

TITLE: M12F Male 05Pin Fixed Socket TO Tin Length(Can Be Customized)

A

B

C

D

E

F

G

H